

# Experiment: The Towers of Hanoi




left

middle

right


# Experiment: The Towers of Hanoi



# Die Türme von Hanoi - So gehts!



left



middle



right

# Die Türme von Hanoi - So gehts!



left




middle




right

# Die Türme von Hanoi - So gehts!




# Die Türme von Hanoi - So gehts!



left




middle




right


# Die Türme von Hanoi - So gehts!




# Die Türme von Hanoi - So gehts!



# Die Türme von Hanoi - So gehts!



# Die Türme von Hanoi - So gehts!




# Die Türme von Hanoi - So gehts!



left



middle




right


# Die Türme von Hanoi - So gehts!



left




middle




right


# Die Türme von Hanoi - So gehts!



# Die Türme von Hanoi - So gehts!




# Die Türme von Hanoi - So gehts!



left




middle




right


# Die Türme von Hanoi - So gehts!



left



middle



right

# Die Türme von Hanoi - So gehts!



left



middle



right

# Die Türme von Hanoi - So gehts!



left




middle




right


# The Towers of Hanoi – Recursive Approach




# The Towers of Hanoi – Recursive Approach




# The Towers of Hanoi – Recursive Approach




# The Towers of Hanoi – Recursive Approach




# The Towers of Hanoi – Recursive Approach




# The Towers of Hanoi – Recursive Approach




# The Towers of Hanoi – Recursive Approach




# The Towers of Hanoi – Recursive Approach




# The Towers of Hanoi – Recursive Approach




# The Towers of Hanoi – Recursive Approach




# The Towers of Hanoi – Recursive Approach




# The Towers of Hanoi – Recursive Approach




# The Towers of Hanoi – Recursive Approach




# The Towers of Hanoi – Recursive Approach




# The Towers of Hanoi – Recursive Approach



# The Towers of Hanoi – Recursive Approach



# The Towers of Hanoi – Code



Move 4 discs from left to right with auxiliary staple middle:

**src      aux      dst**  
`move(4, "left", "middle", "right")`

# The Towers of Hanoi – Code

move( $n$ ,  $src$ ,  $aux$ ,  $dst$ )  $\Rightarrow$  (string)

- 1 Move the top  $n - 1$  discs from  $src$  to  $aux$  with auxiliary staple  $dst$ :

move( $n - 1$ ,  $src$ ,  $dst$ ,  $aux$ );

- 2 Move 1 disc from  $src$  to  $dst$

move(1,  $src$ ,  $aux$ ,  $dst$ );

- 3 Move the top  $n - 1$  discs from  $aux$  to  $dst$  with auxiliary staple  $src$ :

move( $n - 1$ ,  $aux$ ,  $src$ ,  $dst$ );

} else

# The Towers of Hanoi – Code


main():  
move(n,"left","middle","right")

```
void move(int n, const string &src, const string &aux, const string &dst){  
    if (n == 1) {  
        // base case ('move' the disc)  
        std::cout << src << " ---> " << dst << std::endl;  
    } else {  
        // recursive case  
    }  
}
```

*Base case* → src → dst → Base case

# The Towers of Hanoi – Code

```
void move(int n, const string &src, const string &aux, const string &dst){  
    if (n == 1) {  
        // base case ('move' the disc)  
        std::cout << src << " --> " << dst << std::endl;  
    } else {  
        // recursive case  
        move(n-1, src, aux, dst);  
    }  
}
```



# The Towers of Hanoi – Code

```
void move(int n, const string &src, const string &aux, const string &dst){  
    if (n == 1) {  
        // base case ('move' the disc)  
        std::cout << src << " ---> " << dst << std::endl;  
    } else {  
        // recursive case  
        move(n-1, src, dst, aux);  
        move(1, src, aux, dst);  
    }  
}
```

# The Towers of Hanoi – Code

```
void move(int n, const string &src, const string &aux, const string &dst){  
    if (n == 1) {  
        // base case ('move' the disc)  
        std::cout << src << " --> " << dst << std::endl;  
    } else {  
        // recursive case  
        move(n-1, src, dst, aux);  
        move(1, src, aux, dst);  
        move(n-1, aux, src, dst);  
    }  
}
```

1

# The Towers of Hanoi – Code

```
void move(int n, const string &src, const string &aux, const string &dst){  
    if (n == 1) {  
        // base case ('move' the disc)  
        std::cout << src << " --> " << dst << std::endl;  
    } else {  
        // recursive case  
        move(n-1, src, dst, aux);  
        move(1, src, aux, dst);  
        move(n-1, aux, src, dst);  
    }  
}  
  
int main() {  
    move(4, "left", "middle", "right");  
    return 0;  
}
```

# The Towers of Hanoi – Code Alternative

```
void move(int n, const string &src, const string &aux, const string &dst){  
    // base case  
    if (n == 0) return;  
  
    // recursive case  
    move(n-1, src, dst, aux);  
    std::cout << src << " --> " << dst << "\n";  
    move(n-1, aux, src, dst);  
}
```

```
int main() {
    move(4, "left ", "middle", "right");
    return 0;
}
```