

Experiment: The Towers of Hanoi




left

middle

right

Experiment: The Towers of Hanoi



Die Türme von Hanoi - So gehts!



left



middle



right

Die Türme von Hanoi - So gehts!



left




middle



right

Die Türme von Hanoi - So gehts!




Die Türme von Hanoi - So gehts!



left




middle




right


Die Türme von Hanoi - So gehts!




Die Türme von Hanoi - So gehts!



Die Türme von Hanoi - So gehts!



Die Türme von Hanoi - So gehts!




Die Türme von Hanoi - So gehts!



left



middle




right


Die Türme von Hanoi - So gehts!



left




middle




right


Die Türme von Hanoi - So gehts!



Die Türme von Hanoi - So gehts!




Die Türme von Hanoi - So gehts!



left




middle




right


Die Türme von Hanoi - So gehts!



left



middle



right

Die Türme von Hanoi - So gehts!



left



middle



right

Die Türme von Hanoi - So gehts!



left




middle




right


The Towers of Hanoi – Recursive Approach




The Towers of Hanoi – Recursive Approach




The Towers of Hanoi – Recursive Approach




The Towers of Hanoi – Recursive Approach




The Towers of Hanoi – Recursive Approach




The Towers of Hanoi – Recursive Approach




The Towers of Hanoi – Recursive Approach




The Towers of Hanoi – Recursive Approach




The Towers of Hanoi – Recursive Approach




The Towers of Hanoi – Recursive Approach




The Towers of Hanoi – Recursive Approach




The Towers of Hanoi – Recursive Approach




The Towers of Hanoi – Recursive Approach




The Towers of Hanoi – Recursive Approach




The Towers of Hanoi – Recursive Approach



The Towers of Hanoi – Recursive Approach



The Towers of Hanoi – Code



Move 4 discs from left to right with auxiliary staple middle:

```
move(4, "left", "middle", "right")
```

The Towers of Hanoi – Code

`move(n , src , aux , dst)` \Rightarrow

- 1 Move the top $n - 1$ discs from src to aux with auxiliary staple dst :
`move($n - 1$, src , dst , aux);`

- 2 Move 1 disc from src to dst
`move(1, src , aux , dst);`

- 3 Move the top $n - 1$ discs from aux to dst with auxiliary staple src :
`move($n - 1$, aux , src , dst);`

The Towers of Hanoi – Code

```
void move(int n, const string &src, const string &aux, const string &dst){  
    if (n == 1) {  
        // base case ('move' the disc)  
        std::cout << src << " --> " << dst << std::endl;  
    } else {  
        // recursive case  
  
    }  
}
```

The Towers of Hanoi – Code

```
void move(int n, const string &src, const string &aux, const string &dst){  
    if (n == 1) {  
        // base case ('move' the disc)  
        std::cout << src << " --> " << dst << std::endl;  
    } else {  
        // recursive case  
        move(n-1, src, aux, dst);  
  
    }  
}
```

The Towers of Hanoi – Code

```
void move(int n, const string &src, const string &aux, const string &dst){  
    if (n == 1) {  
        // base case ('move' the disc)  
        std::cout << src << " --> " << dst << std::endl;  
    } else {  
        // recursive case  
        move(n-1, src, dst, aux);  
        move(1, src, aux, dst);  
  
    }  
}
```

The Towers of Hanoi – Code

```
void move(int n, const string &src, const string &aux, const string &dst){  
    if (n == 1) {  
        // base case ('move' the disc)  
        std::cout << src << " ---> " << dst << std::endl;  
    } else {  
        // recursive case  
        move(n-1, src, dst, aux);  
        move(1, src, aux, dst);  
        move(n-1, aux, src, dst);  
    }  
}
```

The Towers of Hanoi – Code

```
void move(int n, const string &src, const string &aux, const string &dst){  
    if (n == 1) {  
        // base case ('move' the disc)  
        std::cout << src << " --> " << dst << std::endl;  
    } else {  
        // recursive case  
        move(n-1, src, dst, aux);  
        move(1, src, aux, dst);  
        move(n-1, aux, src, dst);  
    }  
}  
  
int main() {  
    move(4, "left ", "middle", "right ");  
    return 0;  
}
```

The Towers of Hanoi – Code Alternative

```
void move(int n, const string &src, const string &aux, const string &dst){  
    // base case  
    if (n == 0) return;  
  
    // recursive case  
    move(n-1, src, dst, aux);  
    std::cout << src << " --> " << dst << "\n";  
    move(n-1, aux, src, dst);  
}
```

```
int main() {
    move(4, "left ", "middle", "right");
    return 0;
}
```